

NAPO

con cornice

Codice Arcluce **0573004C-840-11**
Q7332-11 SC

Codice driver	Apparecchi collegabili (min-max)	Alimentazione	Watt	Controllo	Class	IP	Peso
1095110A-24V - ex 1095019X	1-30	PRI 220-240V/50-60Hz DC:SEC 24V-CV	16W	ON/OFF	II	IP20	0.11 kg
1095110B-24V	1-30	PRI 220-240V/50-60Hz DC:SEC 24V-CV	16W	DALI	II	IP20	0.11 kg
1095112A-24V	1-30	PRI 220-240V/50-60Hz DC:SEC 24V-CV	16W	ON/OFF	II	IP67	0.11 kg
1095112B-24V	1-30	PRI 220-240V/50-60Hz DC:SEC 24V-CV	16W	DALI	II	IP67	0.11 kg

DRIVER - Tabella di riferimento

Constant current		Electric					Mechanic					Installation					
DRIVER CODE	WIRING	INPUT	OUTPUT	W max	Vf min	Vf max	IP	L (mm)	H (mm)	W (mm)	CEILING CUTOUT (mm)	Max. distance DRIVER-LUMINAIRE (cable section)				Max. quantity for MCB	
												0,5 mm ²	1,0 mm ²	1,5 mm ²	2,5 mm ²	Type B 16A	Type C 16A
1095110A-035	ON/OFF	220-240V 50/60Hz	350	19	2	54	20	52	22	120	55	10	20	50	-	50	85
1095110A-050	ON/OFF	220-240V 50/60Hz	500	20	2	40	20	52	22	120	55	10	20	50	-	50	85
1095110A-070	ON/OFF	220-240V 50/60Hz	700	20	2	29	20	52	22	120	55	10	20	30	50	50	85
1095112A-035	ON/OFF	220-240V 50/60Hz	350	19	2	54	67	91	63	240	100	10	20	50	-	50	85
1095112A-050	ON/OFF	220-240V 50/60Hz	500	20	2	40	67	91	63	240	100	10	20	50	-	50	85
1095112A-070	ON/OFF	220-240V 50/60Hz	700	20	2	29	67	91	63	240	100	10	20	30	50	50	85
1095142A-070	ON/OFF	220-240V 50/60Hz	700	35	10	50	68	80	31	143	86	10	20	30	50	30	50
1095110G-035	ON/OFF-E	220-240V 50/60Hz	350	19	2	54	20	-	-	-	-	10	20	50	-	50	85
1095110G-050	ON/OFF-E	220-240V 50/60Hz	500	20	2	40	20	-	-	-	-	10	20	50	-	50	85
1095110G-070	ON/OFF-E	220-240V 50/60Hz	700	20	2	29	20	-	-	-	-	10	20	30	50	50	85
1095110B-035	DALI	220-240V 50/60Hz	350	17	10	49	20	52	22	120	55	15	-	-	-	50	85
1095110B-050	DALI	220-240V 50/60Hz	500	20	5	40	20	52	22	120	55	15	-	-	-	50	85
1095110B-070	DALI	220-240V 50/60Hz	700	20	3	28	20	52	22	120	55	10	15	-	-	50	85
1095112B-035	DALI	220-240V 50/60Hz	350	17	10	49	67	91	63	240	100	15	-	-	-	50	85
1095112B-050	DALI	220-240V 50/60Hz	500	20	5	40	67	91	63	240	100	15	-	-	-	50	85
1095112B-070	DALI	220-240V 50/60Hz	700	20	3	28	67	91	63	240	100	10	15	-	-	50	85
1095142B-070	DALI	220-240V 50/60Hz	700	35	10	50	68	80	31	143	86	10	15	-	-	30	50
1095110H-035	DALI-E	220-240V 50/60Hz	350	17	10	49	20	-	-	-	-	15	-	-	-	50	85
1095110H-050	DALI-E	220-240V 50/60Hz	500	20	5	40	20	-	-	-	-	15	-	-	-	50	85
1095110H-070	DALI-E	220-240V 50/60Hz	700	20	3	28	20	-	-	-	-	10	15	-	-	50	85
1095130B-035	DALI	220-240V 50/60Hz	4x350	4x8	6	23	67	278	140	95	170	15	-	-	-	20	34
1095131B-035	DALI	220-240V 50/60Hz	4x350	4x12.5	3	45	67	278	140	95	170	15	-	-	-	15	25
1095136B-035	DALI	220-240V 50/60Hz	4x350	4x8+4x8	6	23	67	278	140	95	170	15	-	-	-	15	25
1095130F-035	DMX/RDM	220-240V 50/60Hz	4x350	4x8	6	23	67	278	140	95	170	15	-	-	-	20	34
1095131F-035	DMX/RDM	220-240V 50/60Hz	4x350	4x12.5	2	55	67	278	140	95	170	15	-	-	-	38	38
1095136F-035	DMX/RDM	220-240V 50/60Hz	4x350	4x8+4x8	6	23	67	278	140	95	170	15	-	-	-	15	25

DRIVER - Tabella di riferimento

Constant voltage		Electric					Mechanic					Installation					
DRIVER CODE	WIRING	INPUT	OUTPUT	W max	Vf min	Vf max	IP	L (mm)	H (mm)	W (mm)	CEILING CUTOUT (mm)	Max. distance DRIVER-LUMINAIRE (cable section)				Max. quantity for MCB	
												0,5 mm ²	1,0 mm ²	1,5 mm ²	2,5 mm ²	Type B 16A	Type C 16A
1095110A-24V	ON/OFF	220-240V 50/60Hz	24	16	-	-	20	52	22	120	55	5	10	20	30	50	85
1095112A-24V	ON/OFF	220-240V 50/60Hz	24	16	-	-	67	91	63	240	100	5	10	20	30	50	85
1095110G-24V	ON/OFF-E	220-240V 50/60Hz	24	16	-	-	20	-	-	-	-	5	10	20	30	50	85
1095110B-24V	DALI	220-240V 50/60Hz	24	16	-	-	20	52	22	120	55	5	10	-	-	50	85
1095112B-24V	DALI	220-240V 50/60Hz	24	16	-	-	67	91	63	240	100	5	10	-	-	50	85
1095110H-24V	DALI-E	220-240V 50/60Hz	24	16	-	-	20	-	-	-	-	5	10	-	-	50	85
1095120A-24V	ON/OFF	220-240V 50/60Hz	24	30	-	-	20	38	23	125	42	5	10	20	30	50	100
1095121A-24V	ON/OFF	220-240V 50/60Hz	24	50	-	-	20	59	29	168	66	5	10	20	30	20	34
1095122A-24V	ON/OFF	220-240V 50/60Hz	24	75	-	-	20	61	29	185	68	5	10	20	30	15	25
1095123A-24V	ON/OFF	220-240V 50/60Hz	24	150	-	-	20	60	49	240	80	-	-	5	10	8	13
1095113A-24V	ON/OFF	220-240V 50/60Hz	24	6-60	-	-	67	40	21	240	46	4	8	12	20	13	22
1095114A-24V	ON/OFF	220-240V 50/60Hz	24	10-96	-	-	67	40	23	270	46	2,5	5	7,5	12,5	10	16
1095115A-24V	ON/OFF	220-240V 50/60Hz	24	18-180	-	-	67	60	29	245	68	1,5	2,5	4	7	15	15
1095135B-24V	DALI	220-240V 50/60Hz	4x24	4x7.5	-	-	67	278	140	95	170	5	10	-	-	20	34
1095137B-24V	DALI	220-240V 50/60Hz	4x24	4x35	-	-	67	278	140	95	170	5	10	-	-	8	13
1095135F-24V	DMX/RDM	220-240V 50/60Hz	4x24	4x7.5	-	-	67	278	140	95	170	5	10	-	-	20	34
1095137F-24V	DMX/RDM	220-240V 50/60Hz	4x24	4x35	-	-	67	278	140	95	170	5	10	-	-	8	13